

## BLAST AIR FRESHENER

**Page:** 1

Compilation date: 23/08/2005

Revision date: 09/07/2015

Revision No: 6

## Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BLAST AIR FRESHENER

Product code: AF500

Synonyms: AF500

000769097064

1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane

- Mapplewell
- Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101

Fax: 01226 387100

Email: sales@specialised-aerosols.co.uk

### 1.4. Emergency telephone number

Emergency tel: 07836317118

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; STOT SE 3: H336; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness.

### 2.2. Label elements

Label elements:			
Hazard statements:	H222: Extremely flammable aerosol.		
	H229: Pressurised container: May burst if heated		
	H336: May cause drowsiness or dizziness.		
Signal words:	Danger		
Hazard pictograms:	: GHS02: Flame		
	GHS07: Exclamation mark		



## **BLAST AIR FRESHENER**

# **Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

#### PROPANE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%

## PROPAN-2-OL

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
BUTANE				
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%

### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

## BLAST AIR FRESHENER

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

## **BLAST AIR FRESHENER**

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

8.1. Control parameters

### Hazardous ingredients:

#### PROPANE

Workplace exposure limits:		Re		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1800 mg/m3	7200 mg/m3 -		-
PROPAN-2-O	L			
UK	999 mg/m3	1250 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	-
BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	-

**DNEL/PNEC** Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Protective gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Colourless
Odour:	Pleasant
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Soluble
Flammability limits %: lower:	0.8
Flash point°C:	-10

upper: 19.0

## **BLAST AIR FRESHENER**

**Page:** 5

### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

### Hazardous ingredients:

### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

## Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

## BLAST AIR FRESHENER

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

14.1. UN number

UN number: UN1950

### 14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

### Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

## BLAST AIR FRESHENER

Page: 7

Tunnel code: D

Transport category: 2

## Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

### Section 16: Other information

## Other information

Other information:	: This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	453/2010.		
	* indicates text in the SDS which has changed since the last revision.		
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.		
	H222: Extremely flammable aerosol.		
	H225: Highly flammable liquid and vapour.		
	H229: Pressurised container: May burst if heated		
	H319: Causes serious eye irritation.		
	H336: May cause drowsiness or dizziness.		
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and		
	shall be used only as a guide. This company shall not be held liable for any damage resulting		
	from handling or from contact with the above product.		