



Door Closer DABC inc Semi-Radius Cover, Flatbar Armset – Satin Nickel

Variant code: FL4251.SNP

A heavy duty, but slimline power adjustable overhead door closer, suitable for schools, public buildings, offices, hotels and hospitals.

Features:

- Power size (adjustable by spring)
- EN2 (up to 850mm / 45kg)
- EN3 (up to 950mm / 60kg)
- EN4 (up to 1100mm / 80kg)
- EN5 (up to 1250mm / 110kg)
- Mechanism Rack and Pinion
- Adjustable closing speed
- Adjustable latch action
- Adjustable delayed action
- Adjustable back check
- Max door width (mm) 1250
- Max door weight (kg) 110
- Opening angle 180°
- DDA (Min door width 835mm) Fig 1
- DDA (Min door width 728mm) Fig 66
- LH and RH doors – universal application
- Fire Rated (BS EN 1634-1: 2000)
- CE Marked
- Tested to BS EN1154: 1997
- ANSI tested to 1 million cycles

Please note images are for illustrative purposes only. All products are produced by Rutland however items received may be branded Rutland, Döre or be unbranded.

Property	Value
Warranty (Years)	35
Certification	Certifire, BS EN 1154, BS EN 1634, BS EN 1670 – Grade 5, UKCA, CE
Finish	Satin Nickel
Opening angle (°)	Up to 180°
Max Door Width (mm)	1250
Max Door Weight (kg)	110

Property	Value
Power Size	EN 2-5 Adjustable
Product Type	Overhead Door Closer