Tel: 01626 355177
Email: info@aukhygiene.com




# Numatic WVD2000AP-2 - Wet & Dry Vacuum Cleaner with Pump Out - 240V

**Variant code: 16-WVD2000AP-2/240V**

**Numatic WVD2000AP-2 Wet & Dry Vacuum Cleaner with Pump Out** is a high-capacity industrial wet and dry vacuum cleaner engineered for continuous liquid recovery and demanding commercial cleaning applications. Combining powerful TwinFlo motor performance with a built-in automatic pump-out system, the WVD2000AP-2 delivers exceptional cleaning productivity, heavy-duty durability and reliable wet recovery performance for industrial and professional environments.

Designed for intensive cleaning operations, the WVD2000AP-2 features a huge 70-litre wet collection capacity alongside an automatic pump emptying facility that continuously removes collected liquids during operation. This significantly reduces downtime caused by manual emptying, making the machine ideal for flood recovery, construction environments, industrial maintenance and large-scale wet cleaning tasks. The heavy-duty Structofoam construction in both the head and body provides exceptional durability while remaining lightweight and easy to manoeuvre.

Powered by Numatic's long-life TwinFlo 2-stage bypass motor system, the WVD2000AP-2 delivers strong suction and dependable professional performance in demanding environments. Additional features including the spinning ball safety float valve, trash basket inlet filter and NuCable replaceable cable system improve operational safety, reliability and serviceability. Supplied complete with the professional BS7 accessory kit and stainless steel tube set, this vacuum cleaner provides versatile wet and dry cleaning capability across a wide range of industrial applications.

## Product Features

- **Professional wet & dry vacuum cleaner with pump out**
- Automatic pump emptying system for continuous liquid recovery
- Powerful TwinFlo 2-stage bypass motor

Tel: 01626 355177
Email: info@aukhygiene.com

technology
- Heavy-duty Structofoam head and body construction
- Large 70L wet collection capacity
- Spinning ball safety float valve and trash basket inlet filter
- Supplied with professional BS7 accessory kit and stainless steel tube set
- **NuCable replaceable cable system**

## Product Benefits

- Automatically pumps out liquids during operation for continuous cleaning
- Large capacity reduces downtime and improves productivity
- Heavy-duty Structofoam construction resists industrial wear and damage
- TwinFlo motor system delivers powerful and reliable suction performance
- Lightweight design improves handling and manoeuvrability
- Professional accessories increase cleaning versatility
- Built-in filtration and float systems improve operational safety

## Technical Characteristics

- **TwinFlo 2-stage bypass motor system**
- 70 litre wet collection capacity
- Integrated automatic pump-out functionality
- Heavy-duty Structofoam construction
- Spinning ball safety float valve system
- Trash basket inlet filter protection
- Professional BS7 accessory kit included
- **NuCable plugged replaceable cable system**

## Applications

**Numatic WVD2000AP-2 Wet & Dry Vacuum Cleaner with Pump Out** is ideal for flood recovery, industrial maintenance, warehouses, factories, workshops, construction sites, janitorial services, facilities management teams and contract cleaning companies requiring high-capacity professional wet and dry vacuum cleaning with continuous pump-out capability.

| Property | Value |
| --- | --- |
| Length (mm) | 530 |

Tel: 01626 355177
Email: info@aukhygiene.com

| Property | Value |
| --- | --- |
| Vacuum Motor Wattage (W) | 2x1000W |
| Capacity (L) | 70 |
| Cable Length (m) | 10 |
| Weight (kg) | 38.7 |
| Width (mm) | 640 |
| Height (mm) | 970 |
| Accessories Included with Machine | Hose (NUFLEX) (2.4m), Stainless Steel Bend Tube, Stainless Steel Extension Tube, 400mm ProFlo Wet Floor Tool, 400mm ProFlo Dry Floor Tool |
| Voltage | 230V AC 50/60Hz |
| Noise Level (dB) | 73.7 dB(A) |
| Vacuum Airflow (Litres per Second) | 91 |
| Max Suction H20 (mm) | 2600 |
| Cleaning Range (m) | 26.8 |