



Windmill Relay – Super High Solids Metallised Polish – 5L

Variant code: 03-280

A metallised polish for extreme strength and durability coupled with ease of removability.

Non-yellowing cross linked polymer film. Does not discolour even the lightest floor. Produces a deep shine with excellent slip resistance. Responds brilliantly to all spray burnishing techniques.

For all linoleum, PVC, rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors.

N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring. Always try the chemical in a test area first.

Must be applied to a clean grease free floor. Strip old polish with a suitable polish stripper then rinse thoroughly with clean water, allow the floor to dry. Apply a thin even film of polish using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 mins). May be buffed as required to enhance gloss.

For commercial use only.

Property	Value
Dilution	Use Neat
pH	8.7
Fragrance	Slight
Area of Use	For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo & thermoplastic floors.
How to Use	Apply to clean, grease-free floor. Strip old polish with suitable polish stripper, rinse thoroughly with clean water, allow to dry. Apply thin film of polish using clean, lint-free mop/applicator. Apply second coat when first is dry, approx 30 mins
Chemical Colour	White