



Windmill Relay – Extra High 25% Solids Metallised Polish – 5L

Variant code: 03-280

A metallised polish for extreme strength and durability coupled with ease of removability.

Non-yellowing cross linked polymer film. Does not discolour even the lightest floor. Produces a deep shine with excellent slip resistance. Responds brilliantly to all spray burnishing techniques.

For all linoleum, PVC, rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors.

N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring. Always try the chemical in a test area first.

Must be applied to a clean grease free floor. Strip old polish with a suitable polish stripper then rinse thoroughly with clean water, allow the floor to dry. Apply a thin even film of polish using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 mins). May be buffed as required to enhance gloss.

For commercial use only.

Property	Value
Dilution	Use Neat
Fragrance	Slight
pH	8.7
Area of Use	Polished Hard Floors (Linoleum, PVC, Rubber, Sealed Wood, Terrazzo and Thermoplastic)
Dosing Chart: 10L Dilution	neat
Dosing Chart: 5L Dilution	neat
How to Use	Apply undiluted to a clean, dry, grease-free floor using a lint-free applicator. Strip old polish with a suitable stripper, rinse well, and allow to dry. Apply a thin coat, let dry for 30 minutes, then apply a second coat.
Chemical Colour	White