Tel: 01626 355177
Email: info@aukhygiene.com



Windmill Resilience - Acrylic Base Coat Seal - 2 x 5L

Variant code: 03-381

Windmill Resilience is an acrylic base coat seal designed to provide **strong surface preparation and foundation coating** for floor finishing systems. As part of the Windmill professional floorcare range, it is formulated to improve adhesion, enhance durability and create a consistent base for subsequent floor polish applications.

This acrylic seal works by forming a smooth and even base layer, helping to fill minor surface imperfections and providing a stable platform for top coats. It is particularly effective on porous or worn floor surfaces, where it helps to improve the performance and longevity of metallised polishes and other finishes. By sealing the substrate, it supports better coverage and a more uniform final appearance.

Designed for professional use, Windmill Resilience enables controlled application and build-up, allowing users to prepare floors efficiently before applying finishing coats. The formulation contributes to improved resistance to wear and helps maintain the integrity of the overall floorcare system, especially in high-traffic environments.

Product Features

- Acrylic **base coat seal for floor preparation**
- Provides a smooth and even foundation layer
- Enhances adhesion of floor polishes
- Suitable for **porous and worn floor surfaces**
- Improves overall finish consistency
- Supports professional floorcare systems

Product Benefits

- Extends the life of floor finishes
- Improves appearance of final floor coating
- Reduces risk of uneven polish application
- Enhances durability in high-traffic areas
- Supports efficient floor preparation processes
- Delivers consistent and reliable results

Tel: 01626 355177
Email: info@aukhygiene.com

Technical Characteristics

- Designed for use as a **base coat prior to polishing**
- Suitable for compatible hard floor surfaces
- Can be applied in multiple coats if required
- Requires appropriate floor preparation before use
- Compatible with standard floorcare systems
- Use in accordance with manufacturer guidelines

Applications

Windmill Resilience is suitable for use in **commercial, industrial and institutional environments**, including offices, schools, healthcare facilities and retail spaces. It is particularly effective on **porous or heavily used floors** where a strong base layer is required before applying polish. Its role within a complete floorcare system makes it ideal for achieving **durable, professional-quality finishes** in high-traffic areas.

Property	Value
Fragrance	Characteristic
Dilution	Use Neat
pH	9.2
Area of Use	Floors
How to Use	Apply to clean, grease-free floor. Apply thin film of seal using clean lint free mop/applicator. Apply a second coat when the first is dry, approx 30mins. Coverage 50sqm/L
Chemical Colour	White